TECHNICAL DATA

GIN BONANZA 3 XXS Type designation GIN Bonanza 3 XXS Type test reference no DHV GS-01-2801-23 Holder of certification GIN Gliders Inc. Manufacturer GIN Gliders Inc. **Classification** C Winch towing Yes Number of seats min / max 1/1**Accelerator** Yes **Trimmers** No



BEHAVIOUR AT MIN WEIGHT IN **BEHAVIOUR AT MAX WEIGHT** FLIGHT (60KG) IN FLIGHT (75KG) **Test pilots** Juliette Schönsee **Harald Buntz Expert Josef Bauer** No release No release Inflation/take-off Rising behaviour Overshoots, shall be slowed down to avoid a Easy rising, some pilot correction is front collapse required Special take off technique required No No **Landing** No **Special landing technique required No** Speeds in straight flight Trim speed more than 30 km/h Yes Yes **Speed range using the controls larger than 10** Yes Yes km/h 25 km/h to 30 km/h Minimum speed Less than 25 km/h **Control movement** Symmetric control pressure Increasing Increasing Symmetric control travel 40 cm to 55 cm Greater than 55 cm Pitch stability exiting accelerated flight Α Dive forward angle on exit Dive forward less than 30° Dive forward less than 30° Collapse occurs No No Pitch stability operating controls during accelerated flight Collapse occurs No No Roll stability and damping A **Oscillations** Reducing Reducing Stability in gentle spirals Tendency to return to straight flight Spontaneous exit Spontaneous exit Behaviour exiting a fully developed spiral dive A Initial response of glider (first 180°) Immediate reduction of rate of turn en : keine unmittelbare Reaktion Tendency to return to straight flight Spontaneous exit (g force decreasing, rate of Spontaneous exit (g force decreasing, turn decreasing) rate of turn decreasing) **Turn angle to recover normal flight** Less than 720°, spontaneous recovery Less than 720°, spontaneous recovery Symmetric front collapse Entry Rocking back less than 45° Rocking back less than 45° **Recovery** Spontaneous in less than 3 s Spontaneous in less than 3 s **Dive forward angle on exit** Dive forward 0° to 30° Dive forward 0° to 30° Change of course Keeping course Keeping course Cascade occurs No No Folding lines used yes yes Unaccelerated collapse (at least 50 % chord) | C Rocking back less than 45° Entry Rocking back less than 45° **Recovery** Spontaneous in less than 3 s Spontaneous in less than 3 s **Dive forward angle on exit** Dive forward 0° to 30° Dive forward 30° to 60° Change of course Keeping course Keeping course Cascade occurs No No Folding lines used yes yes Accelerated collapse (at least 50 % chord)

Accelerated collapse (at least 50 % clioid)		
Enti	ry Rocking back less than 45°	Rocking back less than 45°
Recover	ry Spontaneous in less than 3 s	Spontaneous in less than 3 s
Dive forward angle on ex	tit Dive forward 30° to 60°	Dive forward 0° to 30°
Change of cours	se Entering a turn of 90° to 180°	Keeping course
Cascade occur	rs No	No
Folding lines use	ed yes	yes
Exiting deep stall (parachutal stall)	В	В
Exiting deep stall (parachutal stall) Deep stall achieve		B Yes
Deep stall achieve		
Deep stall achieve	ed Yes ry Spontaneous in less than 3 s	Yes
Deep stall achieve Recover Dive forward angle on ex	ed Yes ry Spontaneous in less than 3 s	Yes Spontaneous in less than 3 s
Deep stall achieve Recover Dive forward angle on ex	ed Yes ry Spontaneous in less than 3 s rit Dive forward 30° to 60° se Changing course less than 45°	Yes Spontaneous in less than 3 s Dive forward 30° to 60°
Deep stall achieve Recover Dive forward angle on ex Change of cours	ed Yes ry Spontaneous in less than 3 s rit Dive forward 30° to 60° se Changing course less than 45°	Yes Spontaneous in less than 3 s Dive forward 30° to 60° Changing course less than 45°

High angle of attack recovery

Recovery from a developed full stall

Dive forward angle on exit	Dive forward 30° to 60°	Dive forward 30° to 60°
Collapse	No collapse	No collapse
Cascade occurs (other than collapses)	No	No
Rocking back	Less than 45°	Less than 45°
Line tension	Most lines tight	Most lines tight
Small asymmetric collapse	c	c
Change of course until re-inflation	Less than 90°	Less than 90°
Maximum dive forward or roll angle	Dive or roll angle 15° to 45°	Dive or roll angle 0° to 15°
Re-inflation behaviour	Spontaneous re-inflation	Inflates in less than 3 s from start of pilot action
Total change of course	Less than 360°	Less than 360°

Recovery Spontaneous in less than 3 s

Cascade occurs No

Spontaneous in less than 3 s

collapsed cells with a spontaneous re

No

B

inflation)

Yes

Yes

More than 50 % of the symmetric

Twist occurs No No Cascade occurs No No Folding lines used yes yes Large asymmetric collapse Change of course until re-inflation Less than 90° 90° to 180° **Maximum dive forward or roll angle** Dive or roll angle 15° to 45° Dive or roll angle 15° to 45° **Re-inflation behaviour** Spontaneous re-inflation Inflates in less than 3 s from start of pilot action

Collapse on the opposite side occurs No (or only a small number of collapsed cells No (or only a small number of with a spontaneous re inflation)

Total change of course Less than 360° Less than 360° Collapse on the opposite side occurs No (or only a small number of collapsed cells No (or only a small number of with a spontaneous re inflation) collapsed cells with a spontaneous re inflation) Twist occurs No No Cascade occurs No No Folding lines used yes yes

Small asymmetric collapse accelerated Change of course until re-inflation Less than 90° 90° to 180° **Maximum dive forward or roll angle** Dive or roll angle 15° to 45° Dive or roll angle 15° to 45° **Re-inflation behaviour** Spontaneous re-inflation Inflates in less than 3 s from start of pilot action Total change of course Less than 360° Less than 360° Collapse on the opposite side occurs No (or only a small number of collapsed cells No (or only a small number of with a spontaneous re inflation) collapsed cells with a spontaneous re inflation)

Twist occurs No No Cascade occurs No No Folding lines used yes yes Large asymmetric collapse accelerated Change of course until re-inflation 90° to 180° 90° to 180° **Maximum dive forward or roll angle** Dive or roll angle 15° to 45° Dive or roll angle 15° to 45°

Re-inflation behaviour Spontaneous re-inflation Inflates in less than 3 s from start of pilot action **Total change of course** Less than 360° Less than 360° Collapse on the opposite side occurs No (or only a small number of collapsed cells No (or only a small number of with a spontaneous re inflation) collapsed cells with a spontaneous re inflation) Twist occurs No No Cascade occurs No No Folding lines used yes yes Directional control with a maintained asymmetric collapse

spin travel control travel Trim speed spin tendency Spin occurs No No Α Low speed spin tendency Spin occurs No No Recovery from a developed spin Spin rotation angle after release Stops spinning in 90° to 180° Stops spinning in less than 90° Cascade occurs No No **B-line stall**

Able to keep course Yes

Amount of control range between turn and stall or More than 50 % of the symmetric control

180° turn away from the collapsed side possible in Yes

Not carried out because the manoeuvre is excluded in the user's manual **Big ears Entry procedure** Standard technique Standard technique Behaviour during big ears Stable flight Stable flight Recovery through pilot action in less **Recovery** Recovery through pilot action in less than a

than a further 3 s further 3 s Dive forward 0° to 30° **Dive forward angle on exit** Dive forward 0° to 30° Big ears in accelerated flight **Entry procedure** Standard technique Standard technique **Behaviour during big ears** Stable flight Stable flight **Recovery** Recovery through pilot action in less than a Recovery through pilot action in less than a further 3 s further 3 s **Dive forward angle on exit** Dive forward 0° to 30° Dive forward 0° to 30°

Stable flight Behaviour immediately after releasing the Stable flight accelerator while maintaining big ears Alternative means of directional control 180° turn achievable in 20 s Yes Yes Stall or spin occurs No No

Any other flight procedure and/or configuration described in the user's manual No other flight procedure or configuration described in the user's manual