

DHV TESTREPORT EN926-2:2005

GIN YETI 4 30

Type designation	GIN Yeti 4 30
Type test reference no	DHV GS-01-2191-15
Holder of certification	GIN Gliders Inc.
Manufacturer	GIN Gliders Inc.
Classification	A
Winch towing	Yes
Number of seats min / max	1 / 1
Accelerator	Yes
Trimmers	No



BEHAVIOUR AT MIN WEIGHT IN FLIGHT (95KG)

BEHAVIOUR AT MAX WEIGHT IN FLIGHT (115KG)

Test pilots



Harald Buntz



Sebastian Mackrodt

Inflation/take-off

A

A

Rising behaviour Smooth, easy and constant rising
Special take off technique required No

Smooth, easy and constant rising
No

Landing

A

A

Special landing technique required No

No

Speeds in straight flight

A

A

Trim speed more than 30 km/h Yes
Speed range using the controls larger than 10 km/h Yes

Yes
Yes

Minimum speed Less than 25 km/h

Less than 25 km/h

Control movement

A

A

Symmetric control pressure Increasing
Symmetric control travel Greater than 60 cm

Increasing
Greater than 65 cm

Pitch stability exiting accelerated flight

A

A

Dive forward angle on exit Dive forward less than 30°
Collapse occurs No

Dive forward less than 30°
No

Pitch stability operating controls during accelerated flight

A

A

Collapse occurs No

No

Roll stability and damping

A

A

Oscillations Reducing

Reducing


Stability in gentle spirals

A

A

Tendency to return to straight flight Spontaneous exit

Spontaneous exit

Behaviour in a steeply banked turn 	A	A
Sink rate after two turns	Up to 12 m/s	Up to 12 m/s
Symmetric front collapse	A	A
Entry	Rocking back less than 45°	Rocking back less than 45°
Recovery	Spontaneous in less than 3 s	Spontaneous in less than 3 s
Dive forward angle on exit	Dive forward 0° to 30°	Dive forward 0° to 30°
Change of course	Keeping course	Keeping course
Cascade occurs	No	No
Symmetric front collapse in accelerated flight	A	A
Entry	Rocking back less than 45°	Rocking back less than 45°
Recovery	Spontaneous in less than 3 s	Spontaneous in less than 3 s
Dive forward angle on exit	Dive forward 0° to 30°	Dive forward 0° to 30°
Change of course	Keeping course	Keeping course
Cascade occurs	No	No
Exiting deep stall (parachutal stall)	A	A
Deep stall achieved	Yes	Yes
Recovery	Spontaneous in less than 3 s	Spontaneous in less than 3 s
Dive forward angle on exit	Dive forward 0° to 30°	Dive forward 0° to 30°
Change of course	Changing course less than 45°	Changing course less than 45°
Cascade occurs	No	No
High angle of attack recovery	A	A
Recovery	Spontaneous in less than 3 s	Spontaneous in less than 3 s
Cascade occurs	No	No
Recovery from a developed full stall	A	A
Dive forward angle on exit	Dive forward 0° to 30°	Dive forward 0° to 30°
Collapse	No collapse	No collapse
Cascade occurs (other than collapses)	No	No
Rocking back	Less than 45°	Less than 45°
Line tension	Most lines tight	Most lines tight
Asymmetric collapse 45-50%	A	A
Change of course until re-inflation	Less than 90°	Less than 90°
Maximum dive forward or roll angle	Dive or roll angle 0° to 15°	Dive or roll angle 0° to 15°
Re-inflation behaviour	Spontaneous re-inflation	Spontaneous re-inflation
Total change of course	Less than 360°	Less than 360°
Collapse on the opposite side occurs	No	No
Twist occurs	No	No
Cascade occurs	No	No
Asymmetric collapse 70-75%	A	A
Change of course until re-inflation	Less than 90°	Less than 90°
Maximum dive forward or roll angle	Dive or roll angle 15° to 45°	Dive or roll angle 15° to 45°
Re-inflation behaviour	Spontaneous re-inflation	Spontaneous re-inflation
Total change of course	Less than 360°	Less than 360°
Collapse on the opposite side occurs	No	No
Twist occurs	No	No
Cascade occurs	No	No
Asymmetric collapse 45-50% in accelerated flight	A	A
Change of course until re-inflation	Less than 90°	Less than 90°
Maximum dive forward or roll angle	Dive or roll angle 15° to 45°	Dive or roll angle 0° to 15°
Re-inflation behaviour	Spontaneous re-inflation	Spontaneous re-inflation
Total change of course	Less than 360°	Less than 360°
Collapse on the opposite side occurs	No	No
Twist occurs	No	No
Cascade occurs	No	No
Asymmetric collapse 70-75% in accelerated flight	A	A

Change of course until re-inflation	Less than 90°	Less than 90°
Maximum dive forward or roll angle	Dive or roll angle 15° to 45°	Dive or roll angle 15° to 45°
Re-inflation behaviour	Spontaneous re-inflation	Spontaneous re-inflation
Total change of course	Less than 360°	Less than 360°
Collapse on the opposite side occurs	No	No
Twist occurs	No	No
Cascade occurs	No	No
Directional control with a maintained asymmetric collapse		
Able to keep course	Yes	Yes
180° turn away from the collapsed side possible in 10 s	Yes	Yes
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	More than 50 % of the symmetric control travel
Trim speed spin tendency		
Spin occurs	No	No
Low speed spin tendency		
Spin occurs	No	No
Recovery from a developed spin		
Spin rotation angle after release	Stops spinning in less than 90°	Stops spinning in less than 90°
Cascade occurs	No	No
B-line stall		
Change of course before release	Changing course less than 45°	Changing course less than 45°
Behaviour before release	Remains stable with straight span	Remains stable with straight span
Recovery	Spontaneous in less than 3 s	Spontaneous in less than 3 s
Dive forward angle on exit	Dive forward 0° to 30°	Dive forward 0° to 30°
Cascade occurs	No	No
Big ears		
Entry procedure	Dedicated controls	Dedicated controls
Behaviour during big ears	Stable flight	Stable flight
Recovery	Spontaneous in less than 3 s	Spontaneous in less than 3 s
Dive forward angle on exit	Dive forward 0° to 30°	Dive forward 0° to 30°
Big ears in accelerated flight		
Entry procedure	Dedicated controls	Dedicated controls
Behaviour during big ears	Stable flight	Stable flight
Recovery	Spontaneous in less than 3 s	Spontaneous in less than 3 s
Dive forward angle on exit	Dive forward 0° to 30°	Dive forward 0° to 30°
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	Stable flight
Behaviour exiting a steep spiral		
Tendency to return to straight flight	Spontaneous exit	Spontaneous exit
Turn angle to recover normal flight	Less than 720°, spontaneous recovery	Less than 720°, spontaneous recovery
Sink rate when evaluating spiral stability [m/s]	14	14
Alternative means of directional control		
180° turn achievable in 20 s	Yes	Yes
Stall or spin occurs	No	No
Any other flight procedure and/or configuration described in the user's manual		
No other flight procedure or configuration described in the user's manual		