SKYWALK TEQUILA 6 75 **Type designation** Skywalk Tequila 6 75 Type test reference no DHV GS-01-2831-23 Holder of certification Skywalk GmbH & Co. KG Manufacturer Skywalk GmbH & Co. KG **Classification** B Winch towing Yes Number of seats min / max 1/1**Accelerator** Yes **Trimmers** No

**BEHAVIOUR AT MIN WEIGHT IN** FLIGHT (55KG) **Test pilots** 

**Juliette Schönsee Expert Reiner Brunn** 

No release

Inflation/take-off Rising behaviour Smooth, easy and constant rising **Special take off technique required No** Α

**Landing Special landing technique required No Speeds in straight flight** Trim speed more than 30 km/h Yes

**Speed range using the controls larger than 10** Yes km/h Minimum speed Less than 25 km/h

Control movement Symmetric control pressure Increasing **Symmetric control travel** Greater than 55 cm Pitch stability exiting accelerated flight

**Dive forward angle on exit** Dive forward less than 30° Collapse occurs No Pitch stability operating controls during

Collapse occurs No Roll stability and damping **Oscillations** Reducing

accelerated flight

Stability in gentle spirals

Tendency to return to straight flight Spontaneous exit Behaviour exiting a fully developed spiral dive A

Initial response of glider (first 180°) Immediate reduction of rate of turn **Tendency to return to straight flight** Spontaneous exit (g force decreasing, rate of Spontaneous exit (g force decreasing, turn decreasing) **Turn angle to recover normal flight** Less than 720°, spontaneous recovery

A

**Symmetric front collapse Entry** Rocking back less than 45° **Recovery** Spontaneous in less than 3 s **Dive forward angle on exit** Dive forward 0° to 30° Change of course Entering a turn of less than 90° Cascade occurs No Folding lines used no

Unaccelerated collapse (at least 50 % chord) A **Entry** Rocking back less than 45° **Recovery** Spontaneous in less than 3 s **Dive forward angle on exit** Dive forward 0° to 30° Change of course Entering a turn of less than 90° Cascade occurs No

Folding lines used no Accelerated collapse (at least 50 % chord) B **Entry** Rocking back less than 45° **Recovery** Spontaneous in less than 3 s **Dive forward angle on exit** Dive forward 30° to 60°

Change of course Entering a turn of less than 90° Cascade occurs No Folding lines used no Exiting deep stall (parachutal stall) **Deep stall achieved** Yes

**Recovery** Spontaneous in less than 3 s **Dive forward angle on exit** Dive forward 0° to 30° **Change of course** Changing course less than 45° Cascade occurs No High angle of attack recovery **Recovery** Spontaneous in less than 3 s Cascade occurs No

Recovery from a developed full stall **Dive forward angle on exit** Dive forward 30° to 60° Collapse No collapse Cascade occurs (other than collapses) No **Rocking back** Less than 45° **Line tension** Most lines tight

Small asymmetric collapse

Small asymmetric collapse accelerated

Change of course until re-inflation Less than 90° Maximum dive forward or roll angle Dive or roll angle 0° to 15° **Re-inflation behaviour** Spontaneous re-inflation **Total change of course** Less than 360° Collapse on the opposite side occurs No (or only a small number of collapsed cells No (or only a small number of with a spontaneous re inflation) Twist occurs No

> Cascade occurs No Folding lines used no

Α

Large asymmetric collapse Change of course until re-inflation 90° to 180° **Maximum dive forward or roll angle** Dive or roll angle 15° to 45° **Re-inflation behaviour** Spontaneous re-inflation Total change of course Less than 360° Collapse on the opposite side occurs No (or only a small number of collapsed cells No (or only a small number of

with a spontaneous re inflation) Twist occurs No Cascade occurs No Folding lines used no

Α

Change of course until re-inflation Less than 90° **Maximum dive forward or roll angle** Dive or roll angle 15° to 45° **Re-inflation behaviour** Spontaneous re-inflation Total change of course Less than 360° Collapse on the opposite side occurs No (or only a small number of collapsed cells No (or only a small number of with a spontaneous re inflation) Twist occurs No Cascade occurs No

Folding lines used no

Large asymmetric collapse accelerated Change of course until re-inflation 90° to 180° **Maximum dive forward or roll angle** Dive or roll angle 15° to 45° **Re-inflation behaviour** Spontaneous re-inflation Total change of course Less than 360° Collapse on the opposite side occurs No (or only a small number of collapsed cells No (or only a small number of with a spontaneous re inflation) Twist occurs No

Cascade occurs No Folding lines used no **Directional control with a maintained** asymmetric collapse

**Able to keep course** Yes 180° turn away from the collapsed side possible in Yes Amount of control range between turn and stall or More than 50 % of the symmetric control **spin** travel <u>Trim speed spin tendency</u> Spin occurs No

Low speed spin tendency Spin occurs No Recovery from a developed spin

**Spin rotation angle after release** Stops spinning in less than 90° Cascade occurs No **B-line stall** Change of course before release Changing course less than 45° Behaviour before release Remains stable with straight span

**Recovery** Spontaneous in less than 3 s **Dive forward angle on exit** Dive forward 0° to 30° Cascade occurs No **Big ears Entry procedure** Standard technique

**Behaviour during big ears** Stable flight **Recovery** Spontaneous in less than 3 s **Dive forward angle on exit** Dive forward 0° to 30° Big ears in accelerated flight

**Entry procedure** Standard technique **Behaviour during big ears** Stable flight **Dive forward angle on exit** Dive forward 0° to 30°

Behaviour immediately after releasing the Stable flight accelerator while maintaining big ears

No other flight procedure or configuration described in the user's manual

**Recovery** Spontaneous in less than 3 s

Alternative means of directional control 180° turn achievable in 20 s Yes Stall or spin occurs No

**BEHAVIOUR AT MAX WEIGHT** IN FLIGHT (75KG)

Josef Bauer

No release Smooth, easy and constant rising No A

No Yes Yes Less than 25 km/h

Increasing Greater than 55 cm Dive forward less than 30°

No No

A Spontaneous exit Immediate reduction of rate of turn rate of turn decreasing)

Reducing

Rocking back less than 45° Spontaneous in less than 3 s Dive forward 0° to 30° Keeping course No no

Less than 720°, spontaneous recovery

Rocking back less than 45° Spontaneous in less than 3 s Dive forward 0° to 30° Keeping course No

no

B Rocking back less than 45° Spontaneous in less than 3 s Dive forward 30° to 60° Entering a turn of less than 90° No no

Spontaneous in less than 3 s Dive forward 30° to 60° Changing course less than 45° No Spontaneous in less than 3 s

No B Dive forward 30° to 60° No collapse No

Less than 45°

Most lines tight

Less than 90° Dive or roll angle 0° to 15° Spontaneous re-inflation Less than 360° collapsed cells with a spontaneous re inflation) No No no

90° to 180° Dive or roll angle 15° to 45° Spontaneous re-inflation Less than 360° collapsed cells with a spontaneous re inflation) No No no В

90° to 180°

Dive or roll angle 15° to 45° Spontaneous re-inflation Less than 360° collapsed cells with a spontaneous re inflation) No No no 90° to 180° Dive or roll angle 15° to 45° Spontaneous re-inflation

Less than 360° collapsed cells with a spontaneous re inflation) No No no Yes Yes

No A No Stops spinning in 90° to 180° No

More than 50 % of the symmetric

control travel

Spontaneous in less than 3 s Dive forward 0° to 30° No Standard technique Stable flight Spontaneous in less than 3 s

Changing course less than 45°

Remains stable with straight span

Dive forward 0° to 30° Standard technique Stable flight Spontaneous in less than 3 s

Dive forward 0° to 30° Stable flight

Yes No Any other flight procedure and/or configuration described in the user's manual