DHV-tested Equipment Flying Equipment Database

Manufacturers / Dealers

Flying Schools

Clubs

PRINT OPERATING INSTRUCTION TECHNICAL DATA DHV TESTREPORT LTF DATASHEET PARTS LIST

DHV TESTREPORT LTF

GIN AVID L Type designation	GIN Avid L	
Type test reference no Holder of certification	DHV GS-01-2712-22 GIN Gliders Inc.	
Manufacturer Classification Winch towing		
Number of seats min / max Accelerator	1 / 1 Yes	
Trimmers	No	*
	BEHAVIOUR AT MIN WEIGHT IN FLIGHT (95KG)	BEHAVIOUR AT MAX WEIGHT IN FLIGHT (120KG)
Test pilots		
		25
Inflation/take-off	No release	Mario Eder No release
	Smooth, easy and constant rising	Smooth, easy and constant rising No
		İ A
Special landing technique required		No
Trim speed more than 30 km/h Speed range using the controls larger than 10	Yes	Yes Yes
km/h	Less than 25 km/h	Less than 25 km/h
Control movement Symmetric control pressure	<u> </u>	Ingressing
Symmetric control travel		Increasing Greater than 65 cm
Pitch stability exiting accelerated flight Dive forward angle on exit	<u>:</u>	Dive forward less than 30°
Collapse occurs Pitch stability operating controls during		No
Collapse occurs		No
Roll stability and damping	A	A
Oscillations Stability in gentle spirals		Reducing
Tendency to return to straight flight	<u>i</u>	Spontaneous exit
Behaviour exiting a fully developed spiral dive Initial response of glider (first 180°)	·	A Immediate reduction of rate of turn
Tendency to return to straight flight Turn angle to recover normal flight	Spontaneous exit (g force decreasing, rate of turn decreasing) Less than 720°, spontaneous recovery	Spontaneous exit (g force decreasing, rate of turn decreasing) Less than 720°, spontaneous recovery
		A
Recovery	Rocking back less than 45° Spontaneous in less than 3 s	Rocking back less than 45° Spontaneous in less than 3 s
Dive forward angle on exit Change of course Cascade occurs	Keeping course	Dive forward 0° to 30° Keeping course No
Folding lines used		no
-	Rocking back less than 45° Spontaneous in less than 3 s	Rocking back less than 45° Spontaneous in less than 3 s
Dive forward angle on exit Change of course	Dive forward 0° to 30°	Dive forward 0° to 30° Keeping course
Cascade occurs Folding lines used		No no
	Rocking back less than 45°	Rocking back less than 45°
Dive forward angle on exit		Spontaneous in less than 3 s Dive forward 0° to 30°
Change of course Cascade occurs Folding lines used		Entering a turn of less than 90° No no
		A
Deep stall achieved Recovery Dive forward angle on exit	Spontaneous in less than 3 s	Yes Spontaneous in less than 3 s Dive forward 0° to 30°
	Changing course less than 45°	Changing course less than 45° No
	<u> </u>	A
Recovery Cascade occurs	Spontaneous in less than 3 s No	Spontaneous in less than 3 s No
Recovery from a developed full stall Dive forward angle on exit	·	Dive forward 0° to 30°
Collapse Cascade occurs (other than collapses)	No collapse No	No collapse No
Rocking back Line tension	Less than 45° Most lines tight	Less than 45° Most lines tight
Small asymmetric collapse Change of course until re-inflation		Less than 90°
	Spontaneous re-inflation	Dive or roll angle 0° to 15° Spontaneous re-inflation Less than 360°
Total change of course Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous re inflation)	
Twist occurs Cascade occurs		No No
Folding lines used <u>Large asymmetric collapse</u>		no A
Change of course until re-inflation Maximum dive forward or roll angle	Less than 90°	Less than 90° Dive or roll angle 15° to 45°
Re-inflation behaviour Total change of course	Spontaneous re-inflation Less than 360°	Spontaneous re-inflation Less than 360°
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous re inflation)	No (or only a small number of collapsed cells with a spontaneous re inflation)
Twist occurs Cascade occurs Folding lines used	No	No No no
		A
Change of course until re-inflation Maximum dive forward or roll angle	Dive or roll angle 15° to 45°	Less than 90° Dive or roll angle 15° to 45°
Total change of course	Spontaneous re-inflation Less than 360° No (or only a small number of collapsed cells	Spontaneous re-inflation Less than 360° No (or only a small number of
Twist occurs	with a spontaneous re inflation) No	collapsed cells with a spontaneous re inflation) No
Cascade occurs Folding lines used		No no
		Less than 90°
Change of course until re-inflation Maximum dive forward or roll angle Re-inflation behaviour		Dive or roll angle 15° to 45° Spontaneous re-inflation
Total change of course Collapse on the opposite side occurs	Less than 360° No (or only a small number of collapsed cells with a spontaneous re inflation)	collapsed cells with a spontaneous re
Twist occurs Cascade occurs	No	inflation) No No
Folding lines used		no no
Directional control with a maintained asymmetric collapse		Voc.
Able to keep course	Yes	Yes Yes
180° turn away from the collapsed side possible in 10 s		M 50.0/ 6.11
180° turn away from the collapsed side possible in 10 s Amount of control range between turn and stall or	More than 50 % of the symmetric control travel	More than 50 % of the symmetric control travel
180° turn away from the collapsed side possible in 10 s Amount of control range between turn and stall or spin	travel	•
180° turn away from the collapsed side possible in 10 s Amount of control range between turn and stall or spin Trim speed spin tendency Spin occurs Low speed spin tendency	A No	control travel A No
180° turn away from the collapsed side possible in 10 s Amount of control range between turn and stall or spin Trim speed spin tendency Spin occurs Low speed spin tendency Spin occurs	A No	control travel A No No
180° turn away from the collapsed side possible in 10 s Amount of control range between turn and stall or spin Frim speed spin tendency Spin occurs Low speed spin tendency Spin occurs	A No A No Stops spinning in less than 90°	control travel A No

Alternative means of directional control Α 180° turn achievable in 20 s Yes Stall or spin occurs No Any other flight procedure and/or configuration described in the user's manual

No other flight procedure or configuration described in the user's manual

Behaviour immediately after releasing the Stable flight accelerator while maintaining big ears

B-line stall

Big ears

Big ears in accelerated flight

Α

¦Β

Entry procedure Standard technique

Α

Entry procedure Standard technique

Behaviour before release Remains stable with straight span

Recovery Spontaneous in less than 3 s

Recovery Spontaneous in 3 s to 5 s

Recovery Spontaneous in 3 s to 5 s

Change of course before release Changing course less than 45°

Dive forward angle on exit Dive forward 0° to 30°

Dive forward angle on exit Dive forward 0° to 30°

Dive forward angle on exit Dive forward 0° to 30°

Cascade occurs No

Behaviour during big ears Stable flight

Behaviour during big ears Stable flight

Α

No

Α

Changing course less than 45°

Spontaneous in less than 3 s

Spontaneous in less than 3 s

Spontaneous in less than 3 s

Dive forward 0° to 30°

Standard technique

Dive forward 0° to 30°

Standard technique

Dive forward 0° to 30°

Stable flight

Stable flight

Stable flight

Α

Yes

No

Remains stable with straight span