DHV TESTREPORT LTF

OPERATING INSTRUCTION

PRINT

Less than 720°, spontaneous recovery

Flying Schools

Clubs

DHV Databases

TECHNICAL DATA

DHV TESTREPORT LTF

DATASHEET

PARTS LIST

Test pilots		
	BEHAVIOUR AT MIN WEIGHT IN FLIGHT (50KG)	BEHAVIOUR AT MAX WEIGHT IN FLIGHT (80KG)
Trimmers	No	
Accelerator	Yes	是这种是一个人的。 第一个人的一个人的一个人的一个人的一个人的一个人的一个人的一个人的一个人的一个人的
Number of seats min / max	1 / 1	
Winch towing	Yes	
Classification	В	
Manufacturer	Skywalk GmbH & Co. KG	
Holder of certification	Skywalk GmbH & Co. KG	
Type test reference no	DHV GS-01-2399-18	
Type designation	Skywalk Arak XXS	, Ly
SKYWALK ARAK XXS		

	BEHAVIOUR AT MIN WEIGHT IN FLIGHT (50KG)	BEHAVIOUR AT MAX WEIGHT IN FLIGHT (80KG)
Test	pilots Harald Buntz	Beni Stocker
	No release	No release
Inflation/take-off	A	A
Rising beha	aviour Smooth, easy and constant rising	Smooth, easy and constant rising
Special take off technique red	quired No	No

Special take off technique required	No	No
<u>Landing</u>	A	A
Special landing technique required	No	No
<u>Speeds in straight flight</u>	A	¦A
Trim speed more than 30 km/h	Yes	Yes

Speeds in straight flight	A	A
Trim spe	eed more than 30 km/h Yes	Yes
Speed range using the	controls larger than 10 Yes km/h	Yes
	Minimum speed Less than 25 km/h	Less than 25 km/h
Control movement	Α	Α
Symi	metric control pressure Increasing	Increasing
Sy	mmetric control travel Greater than 55 cm	Greater than 60 cm

Pitch stability exiting accelerated flight Α Dive forward less than 30° **Dive forward angle on exit** Dive forward less than 30° Collapse occurs No No

Pitch stability operating controls during Α accelerated flight Collapse occurs No No Roll stability and damping

Oscillations Reducing Reducing Stability in gentle spirals Tendency to return to straight flight Spontaneous exit Spontaneous exit Behaviour exiting a fully developed spiral dive A Initial response of glider (first 180°) Immediate reduction of rate of turn Immediate reduction of rate of turn Tendency to return to straight flight Spontaneous exit (g force decreasing, rate of Spontaneous exit (g force decreasing, turn decreasing) rate of turn decreasing)

Turn angle to recover normal flight Less than 720°, spontaneous recovery

Cascade occurs No

Α Symmetric front collapse **Entry** Rocking back less than 45° Rocking back less than 45° Spontaneous in less than 3 s **Recovery** Spontaneous in less than 3 s **Dive forward angle on exit** Dive forward 0° to 30° Dive forward 0° to 30° **Change of course** Entering a turn of less than 90° Entering a turn of less than 90° Cascade occurs No No

Folding lines used no no Unaccelerated collapse (at least 50 % chord) | B **Entry** Rocking back less than 45° Rocking back less than 45° **Recovery** Spontaneous in 3 s to 5 s Spontaneous in 3 s to 5 s **Dive forward angle on exit** Dive forward 30° to 60° Dive forward 30° to 60° Change of course Entering a turn of less than 90° Entering a turn of less than 90°

Cascade occurs No No Folding lines used no no Accelerated collapse (at least 50 % chord) B **Entry** Rocking back less than 45° Rocking back less than 45° **Recovery** Spontaneous in 3 s to 5 s Spontaneous in 3 s to 5 s **Dive forward angle on exit** Dive forward 30° to 60° Dive forward 30° to 60° Change of course Entering a turn of less than 90° Entering a turn of less than 90°

No

No collapse

Less than 360°

Spontaneous re-inflation

Folding lines used no no Exiting deep stall (parachutal stall) Α **Deep stall achieved** Yes Yes **Recovery** Spontaneous in less than 3 s Spontaneous in less than 3 s **Dive forward angle on exit** Dive forward 0° to 30° Dive forward 0° to 30° Change of course Changing course less than 45° Changing course less than 45° Cascade occurs No

High angle of attack recovery **Recovery** Spontaneous in less than 3 s Spontaneous in less than 3 s Cascade occurs No No Recovery from a developed full stall Dive forward angle on exit Dive forward 0° to 30° Dive forward 0° to 30°

Collapse No collapse

Total change of course Less than 360°

Cascade occurs (other than collapses) No No Rocking back Less than 45° Less than 45° **Line tension** Most lines tight Most lines tight Small asymmetric collapse Change of course until re-inflation Less than 90° Less than 90° Dive or roll angle 15° to 45° **Maximum dive forward or roll angle** Dive or roll angle 15° to 45° **Re-inflation behaviour** Spontaneous re-inflation Spontaneous re-inflation

Collapse on the opposite side occurs No (or only a small number of collapsed cells No (or only a small number of with a spontaneous re inflation) collapsed cells with a spontaneous re inflation) No Twist occurs No Cascade occurs No No Folding lines used no no Large asymmetric collapse Change of course until re-inflation Less than 90° Less than 90° Maximum dive forward or roll angle Dive or roll angle 15° to 45° Dive or roll angle 15° to 45°

Re-inflation behaviour Spontaneous re-inflation **Total change of course** Less than 360° Less than 360° Collapse on the opposite side occurs No (or only a small number of collapsed cells No (or only a small number of with a spontaneous re inflation) collapsed cells with a spontaneous re inflation) No Twist occurs No Cascade occurs No No Folding lines used no no

Small asymmetric collapse accelerated Α Change of course until re-inflation Less than 90° Less than 90° Dive or roll angle 15° to 45° **Maximum dive forward or roll angle** Dive or roll angle 15° to 45° **Re-inflation behaviour** Spontaneous re-inflation Spontaneous re-inflation Less than 360° Total change of course Less than 360° Collapse on the opposite side occurs No (or only a small number of collapsed cells No (or only a small number of collapsed cells with a spontaneous re with a spontaneous re inflation) inflation) Twist occurs No No

Cascade occurs No No Folding lines used no no Large asymmetric collapse accelerated Change of course until re-inflation 90° to 180° 90° to 180° **Maximum dive forward or roll angle** Dive or roll angle 15° to 45° Dive or roll angle 15° to 45° **Re-inflation behaviour** Spontaneous re-inflation Spontaneous re-inflation Total change of course Less than 360° Less than 360° Collapse on the opposite side occurs No (or only a small number of collapsed cells No (or only a small number of with a spontaneous re inflation) collapsed cells with a spontaneous re inflation) Twist occurs No No No Cascade occurs No

Folding lines used no no Directional control with a maintained Α Α asymmetric collapse Able to keep course Yes Yes **180° turn away from the collapsed side possible in** Yes Yes Amount of control range between turn and stall or More than 50 % of the symmetric control More than 50 % of the symmetric spin travel control travel

Trim speed spin tendency **Spin occurs** No No Low speed spin tendency

Spin occurs No

Change of course before release Changing course less than 45°

No other flight procedure or configuration described in the user's manual

B-line stall

Α Recovery from a developed spin Stops spinning in less than 90° Spin rotation angle after release Stops spinning in less than 90° Cascade occurs No No

No

Changing course less than 45°

Behaviour before release Remains stable with straight span Remains stable with straight span **Recovery** Spontaneous in less than 3 s Spontaneous in less than 3 s Dive forward angle on exit Dive forward 30° to 60° Dive forward 30° to 60° Cascade occurs No No <u>Big ears</u> **Entry procedure** Dedicated controls **Dedicated controls**

Behaviour during big ears Stable flight Stable flight **Recovery** Spontaneous in 3 s to 5 s Spontaneous in less than 3 s Dive forward 0° to 30° **Dive forward angle on exit** Dive forward 0° to 30° Big ears in accelerated flight **Entry procedure** Dedicated controls Dedicated controls Behaviour during big ears Stable flight Stable flight **Recovery** Spontaneous in 3 s to 5 s Spontaneous in less than 3 s

Dive forward angle on exit Dive forward 0° to 30° Dive forward 0° to 30° Stable flight Behaviour immediately after releasing the Stable flight accelerator while maintaining big ears Α Alternative means of directional control 180° turn achievable in 20 s Yes Yes

Stall or spin occurs No No Any other flight procedure and/or configuration described in the user's manual